


NM1- 230V 50 Hz Technical Data

Nominal voltage & frequency	230V-50Hz
Power supply tolerance	207V~253V
Number of cable cores	4
Insulation class	H / I
Wire section	0.75mm ²
Type of limit switch	Progressive limit switch
Capacity of LSU	30 turns
Repeatability	±5°
System of protection	IP44
Working temperature	-10°C to 40°C
Noise level	For information only factory measurement process at 1m away and without load

Description	Nominal torque (Nm)	Nominal speed (Rpm)	L1 max (mm)	L2 max (mm)	Rated power (W)	Rated current (A)	Thermal tripping (°C)	Brake type -	Weight (Kg)	Duty cycle	Noise (dBA)
NM1/20-16	20	16	622	575	170	0.8	140	Cam	3.14	4min	45
NM1/30-16	30	16	652	605	240	1.1	140	Cam	3.4	4min	45
NM1/30-12	30	12	652	605	200	0.9	140	Cam	3.46	4min	45
NM1/40-12	40	12	652	605	240	1.1	140	Cam	3.5	4min	45
NM1/50-12	50	12	652	605	270	1.2	160	Cam	3.51	4min	45



Marketing Name:		R&D Name:		Quality Name:	
Date:		Date:		Date:	