

NP45 RS-230V 50Hz Technical Data

Nominal voltage & frequency	230V-50Hz
Power supply tolerance	207V~253V
Number of cable cores	4
Insulation class	H / I
Wire section	0.5 mm ²
Type of limit switch	Special limit electronic adjustment
Capacity of LSU	infinite
Repeatability	±5°
System of protection	IP44
Working temperature	0°C to 50°C
Noise level	For information only factory measurement process at 1m away and without load

Description	Nominal torque (Nm)	Nominal speed (Rpm)	L1 max (mm)	L2 max (mm)	Rated power (W)	Rated current (A)	Thermal tripping (°C)	Brake type -	Weight (Kg)	Duty cycle	Noise (dBA)
NP45 RS/10-16	10	16	636	606	120	0.55	160	Cam	2.5	4min	45
NP45 RS/15-16	15	16	666	636	150	0.7	140	Cam	2.7	4min	45
NP45 RS/20-16	20	16	666	636	170	0.8	140	Cam	2.7	4min	45
NP45 RS/30-16	30	16	696	666	240	1.1	140	Cam	3	4min	45
NP45 RS/40-12	40	12	696	666	240	1.1	140	Cam	3	4min	45
NP45 RS/50-12	50	12	696	666	270	1.12	160	Cam	3	4min	45

